

25X1

August 28th, 1958

25X1

Att: [] - Senior Project Engineer

ORIGINAL CL BY 23 59 79
☐ DECL ☒ REVW ON 21/07/2010
 EXT DYND GARS BY SAME
 REASON 3 d (3)

25X1

Dear Sir:

We are writing you at the request of [] our Applications Engineer who has discussed these matters with you.

25X1

In an ambient temperature range of 40 - 90^o F we would expect approximately normal shelf life with somewhat better charge retention at the lower temperature. This would be as follows:

Button cells and VO sealed cells

2 weeks - 75% - 30 days - 60% - 90 days - 40%

If vented VO cells are used there is substantial improvement as follows:

2 weeks - 85% - 30 days - 70% - 90 days - 60%

In regard to the rating of our button type cells these are conservative and can be substantially exceeded under conditions of very long low rate charging and low rate discharging. However, since various applications may involve their use under varying conditions the ratings are established so that they can be achieved under unknown conditions of operation.

We would not recommend the use of Mylar as a means of constricting button cells even though only 2 or 3 charging cycles are contemplated. However, if the cells were connected with welded connectors and placed in an enclosure which was insulated and also restricted their expansion in a direction perpendicular to their diameter, this would offer the minimum possible dimensions and weight.

25X1

We trust the above is of assistance to you. Should you require any further information, please feel free to contact us or []

25X1

Very truly yours,

25X1

008632

DOC 48	REV DATE 21 JULY 80	BY 057447
ORIG COMP 056	SPI 56	TYPE 01
ORIG CLASS 41	PAGES 1	REV CLASS C
JULY 23	NEXT REV 2010	AUTH: HR 10-2

CONFIDENTIAL